

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
20.000	94.00	H-40	520	1530	1530		1530	581		1041	1077	0.438	19.124	18.936	
20.000	94.00	J-55	520	2110	2110	2110	2110	783	907	1402	1480	0.438	19.124	18.936	
20.000	94.00	K-55	520	2110	2110	2110	2110	824	955	1479	1480	0.438	19.124	18.936	
20.000	106.50	J-55	770	2410	2410	2410	2410	913	1056	1595	1685	0.500	19.000	18.812	
20.000	106.50	K-55	770	2410	2410	2410	2410	960	1113	1683	1685	0.500	19.000	18.812	
20.000	106.50	N-80	770	3500	3500	3500	3500	1307	1514	2281	2450	0.500	19.000	18.812	
20.000	133.00	K-55	1500	3060	3060	3060	3060	1253	1453	2123	2125	0.635	18.730	18.542	
20.000	133.00	L-80	1600	4450	4450	4450	4450	1692	1958	2849	3091	0.635	18.730	18.542	
20.000	133.00	N-80	1600	4450	4450	4450	4450	1707	1976	2877	3091	0.635	18.730	18.542	
20.000	169.00	K-55	2500	3910	3230	3430	3380	1402	1732	2689	2692	0.812	18.376	18.188	
20.000	169.00	L-80	3020	5680	4690	4990	4920	2202	2549	3610	3916	0.812	18.376	18.188	
20.000	169.00	N-80	3020	5680	4690	4990	4920	2221	2573	3645	3916	0.812	18.376	18.188	