

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
4.500	9.50	J-55	3310	4380	4380			101			152	0.205	4.090	3.965	
4.500	9.50	K-55	3310	4380	4380			112			152	0.205	4.090	3.965	
4.500	10.50	J-55	4010	4790	4790		4790	132		203	166	0.224	4.052	3.927	
4.500	10.50	K-55	4010	4790	4790		4790	146		249	166	0.224	4.052	3.927	
4.500	11.60	J-55	4960	5350	5350	5350	5350	154	162	225	184	0.250	4.000	3.875	
4.500	11.60	K-55	4960	5350	5350	5350	5350	170	180	277	184	0.250	4.000	3.875	
4.500	11.60	L-80	6350	7780		7780	7780		212	291	267	0.250	4.000	3.875	
4.500	11.60	HCL-80	8650	7780		7780	7780		223	312	267	0.250	4.000	3.875	
4.500	11.60	N-80	6350	7780		7780	7780		223	304	267	0.250	4.000	3.875	
4.500	11.60	HCN-80	8650	7780		7780	7780		223	312	267	0.250	4.000	3.875	
4.500	11.60	C-90	6810	8750		8750	8750		223	309	300	0.250	4.000	3.875	
4.500	11.60	S-95	8650	9240		9240	9240		245	338	317	0.250	4.000	3.875	
4.500	11.60	T-95	7030	9240		9240	9240		234	325	317	0.250	4.000	3.875	
4.500	11.60	C-95	7030	9240		9240	9240		234	325	317	0.250	4.000	3.875	
4.500	11.60	HCP-110	8650	10690		10690	10690		279	385	367	0.250	4.000	3.875	
4.500	11.60	P-110	7580	10690		10690	10690		279	385	367	0.250	4.000	3.875	
4.500	13.50	L-80	8540	9020		9020	9020		257	334	307	0.290	3.920	3.795	
4.500	13.50	HCL-80	10380	9020		9020	9020		270	359	307	0.290	3.920	3.795	
4.500	13.50	N-80	8540	9020		9020	9020		270	349	307	0.290	3.920	3.795	
4.500	13.50	HCN-80	10380	9020		9020	9020		270	359	307	0.290	3.920	3.795	
4.500	13.50	C-90	9300	10150		10150	10150		270	355	345	0.290	3.920	3.795	
4.500	13.50	S-95	10380	10710		10710	10710		297	388	364	0.290	3.920	3.795	
4.500	13.50	T-95	9660	10710		10710	10710		284	374	364	0.290	3.920	3.795	
4.500	13.50	C-95	9660	10710		10710	10710		284	374	364	0.290	3.920	3.795	
4.500	13.50	P-110	10680	12410		12410	12410		338	443	422	0.290	3.920	3.795	
4.500	15.10	L-80	11090	10480		10480	10480		308	384	353	0.337	3.826	3.701	
4.500	15.10	HCL-80	12330	10480		10480	9790		325	408	353	0.337	3.826	3.701	
4.500	15.10	S-95	12330	12450		12450	11630		357	446	419	0.337	3.826	3.701	
4.500	15.10	P-110	14350	14420		14420	13460		406	509	485	0.337	3.826	3.701	
4.500	15.10	Q-125	15840	16380		16380	15300		438	554	551	0.337	3.826	3.701	
4.500	15.10	V-150	18110	19660		19660	18360		519	658	661	0.337	3.826	3.701	