

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
6.625	20.00	H-40	2520	3040	3040			184			229	0.288	6.049	5.924	
6.625	20.00	J-55	2970	4180	4180	4180	4180	245	266	374	315	0.288	6.049	5.924	
6.625	20.00	K-55	2970	4180	4180	4180	4180	267	290	453	315	0.288	6.049	5.924	
6.625	24.00	J-55	4560	5110	5110	5110	5110	314	340	453	382	0.352	5.921	5.796	
6.625	24.00	K-55	4560	5110	5110	5110	5110	342	372	548	382	0.352	5.921	5.796	
6.625	24.00	L-80	5760	7440		7440	7440		473	592	555	0.352	5.921	5.796	
6.625	24.00	N-80	5760	7440		7440	7440		481	615	555	0.352	5.921	5.796	
6.625	24.00	C-90	6140	8370		8370	8370		520	633	624	0.352	5.921	5.796	
6.625	24.00	C-95	6310	8830		8830	8830		546	665	659	0.352	5.921	5.796	
6.625	24.00	P-110	6730	10230		10230	10230		641	786	763	0.352	5.921	5.796	
6.625	28.00	L-80	8170	8810		8810	8810		576	693	651	0.417	5.791	5.666	
6.625	28.00	N-80	8170	8810		8810	8810		586	721	651	0.417	5.791	5.666	
6.625	28.00	C-90	8880	9910		9910	9910		633	742	732	0.417	5.791	5.666	
6.625	28.00	C-95	9220	10460		10460	10460		665	780	773	0.417	5.791	5.666	
6.625	28.00	P-110	10160	12120		12120	12120		781	922	895	0.417	5.791	5.666	
6.625	32.00	L-80	10320	10040		10040	9820		666	783	734	0.475	5.675	5.550	
6.625	32.00	N-80	10320	10040		10040	9820		677	814	734	0.475	5.675	5.550	
6.625	32.00	C-90	11330	11290		11290	11050		732	837	826	0.475	5.675	5.550	
6.625	32.00	C-95	11810	11920		11920	11660		769	880	872	0.475	5.675	5.550	
6.625	32.00	P-110	13220	13800		13800	13500		904	1040	1009	0.475	5.675	5.550	
6.625	32.00	Q-125	14530	15680		15680	15340		989	1138	1147	0.475	5.675	5.550	